

FIRE ROLLER SHUTTER A-60 SLIMLINE FABRIC

PRODUCT OVERVIEW









Safety

- Curtain made of high-temp, resistant fabric
- > Fall arrestor according to FN 12604
- > Shutter will close without electrical power in case of fire (gravity failsafe).
- Release device delivered with backup batter to keep the shutter open, even in case of main power supply failure for up to 1 hour.
- Shutter only for bulkhead closure.

Interface

- Connection to Central Fire Alarm system
 - > Open indication
 - Close indication
 - > General alarm
 - > Remote closing


Sarvicas

- Pre-assembled for simplified installation.
- > Including technical evaluation of requirement
- Worldwide installation according to our service conditions, if required.
- Worldwide service and supply of spare parts, maintenance and repair.

Documentation

- > Certificates
- (DNV Module B & D. SDoC. DoC
- Instruction manuals
- > Maintenance manual
- > Drawings
- Spare part lists

FIRE ROLLER SHUTTER A-60 SLIMLINE FABRIC



1	Guide
---	-------

- ② Fall arrester
- ③ Drive
- Pneumatic reset system
- Siren with flashlight
- Receiver safety contact bar
- Transformer with main switch
- ® Control unit
- Release button
- @ Key switch (1/ 0/ 2)
- ff Transmitter safety contact bar
- Safety contact bar

Power supply

Operation voltage:
Closing speed
Max 15 cm/s

Available materials:	> Galvanized steel > AISI 304
Drive type:	Chain-drive
Size range	
Min. size:	c/o 1.000 mm x c/h 1.000 mm
Max.size:	c/o 4.360 mm x c/h 4.150 mm
Max.surface:	18 m²

Technical details

Certification	
Module B	MEDB00002YA
Module D	MEDD00000DN

Picture shows Fire Roller Shutter A-60 SlimLine Fabric with chain drive. Smaller versions are available with tubular drive.

The fire protection must give the emergency services the possibility to fight against the fire.

To ensure this KAFFER offers an array of solutions.

To ensure this, KAEFER offers an array of solutions, which meet the highest quality and safety standards for fire protection.

Fire Safety Products from KAEFER are used on more than 600 vessels (cruise ships, mega yachts, ferries).

All products complies the Hong Kong International Convention requirements.







400/440 VAC. 50/60 Hz



Contac

KAEFER Schiffsausbau GmbH Getreidestr. 3 28217 Bremen Mr. Jan-Timo Kolthammei +49 421 6109 199 firedoors@kaefer.com



